

WASHINGTON DEPARTMENT OF ECOLOGY
ENVIRONMENTAL ASSESSMENT PROGRAM
FRESHWATER MONITORING UNIT
STREAM DISCHARGE TECHNICAL NOTES

STATION ID: 19C060
STATION NAME: West Twin River
WATER YEAR: 2010
AUTHOR: Casey Clishe

Introduction

Watershed Description

The West Twin River station is a stand-alone, continuously recording gaging station that has been operating since June 2004 in Water Resource Inventory Area (WRIA) 19. Like the other two drainages within the Strait of Juan de Fuca complex (East Twin River and Deep Creek) , West Twin River is very dynamic and carries substantial loads of bed material and large woody debris during precipitation--driven storm events which typically occur from November through February. The basin geology is composed of Crescent Formation volcanic rock in the upper watershed, marine sedimentary rock in the lower watershed, and terraces of glacial deposits in the lower floodplain (ONF 2002).

Gage Location

The gaging station is located in Clallam County, Washington approximately 20 miles west of Port Angeles. The station is on the left bank approximately 0.2 miles upstream from the mouth.

Table 1. Basin Area and Legal Description

Drainage Area (square miles)	12.7
Latitude (degrees, minutes, seconds)	48 09 47
Longitude (degrees, minutes, seconds)	123 57 10

Table 2. Discharge Statistics.

Mean Annual Discharge (cfs)	47
Median Annual Discharge (cfs)	38
Maximum Daily Mean Discharge (cfs)	237
Minimum Daily Mean Discharge (cfs)	2.1
Maximum Instantaneous Discharge (cfs)	339
Minimum Instantaneous Discharge (cfs)	1.2
Discharge Equaled or Exceeded 10 % of Recorded Time (cfs)	126
Discharge Equaled or Exceeded 90 % of Recorded Time (cfs)	3.4
Number of Days Discharge is Greater Than Range of Ratings	22
Number of Days Discharge is Less Than Range of Ratings	0
Number of Un-Reported Days	22
Number of Days Qualified as Estimates	67
Number of Modeled Days	0

Note: Statistics displayed in Table 2 may not include values in which the predicted discharge exceeds the range of ratings.

Table 2 Discussion (Discharge Statistics)

Twenty--two total days were not factored into the discharge statistics reported in Table 2. These 22 days were some of the highest discharge values recorded during the water year, so actual values were higher than those reported in the table. An unusually high number of days were quality coded estimated due to exceedances of the logger drift error thresholds. Two moderately--large to large hydrologic events occurred in November 2009. Six to seven moderate events punctuated the remainder of the winter months. A moderately large event in late March 2010 assisted in elevating flows through the spring. A steady decline to baseflow began in June. Extreme low--flow conditions persisted in September until a freshet late in the month elevated baseflows for the remainder of the water year.

Table 3. Error Analysis Summary.

Potential Logger Drift Error (% of discharge)	30.2
Potential Weighted Rating Error (% of discharge)	10.0
Total Potential Error (% of discharge)	40.2

Table 3 Discussion (Error Analysis)

Total Potential Error (TPE) is the cumulative value of the potential logger drift error and the potential weighed rating error. Error surrounding any predicted discharge value is acquired in a number of ways, ranging from variability in the quality of any particular discrete discharge measurement to the operational performance of a datalogger and the sonde measuring stage. Total Potential Error defines the expected range for any predicted discharge value. For example, if the TPE is 10.0 % and the predicted discharge value is 100 cfs, the range in which the actual predicted value lies is 90 to 110 cfs. For 177 of the recorded days, the agreement between the stage on the logger and discrete observations of the primary gage index met standards defining stable drift. Sixty-seven days were quality coded as estimated due to logger drift error exceedances.

Table 4. Stage Record Summary

Minimum Recorded Stage (feet)	2.44
Maximum Recorded Stage (feet)	7.20
Range of Recorded Stage (feet)	4.76

Table 4 Discussion (Stage Record)

The quality of the stage record for WY2010 was compromised by unusually large and somewhat random discrepancies between the observed primary gage index and the continuous stage record. This results in high logger drift error values and is most commonly recorded during baseflow months when small differences in stage between the PGI and the logged stage result in large differences in percent discharge. The record was continuous and complete except for a single missing day that was filled using regressed, well--correlated stage data from a nearby station. During WY2010, discrepancies between the observed value of the primary gage index and the logged stage value were reconciled by automated adjustment of the stage record using the data shift function. The maximum stage value was recorded on November 20, 2009. The minimum stage value was recorded on October 10, 2009.

Table 5. Rating Table Summary

Rating Table No.	9	10	11
Period of Ratings	10/01-11/25	11/20-03/29	3/28-09/14
Range of Ratings (cfs)	0.001-381	0.001-397	0.001-331
No. of Defining Measurements	12	7	7
Rating Error (%)	8.9	9.0	11.4

Rating Table No.	101		
Period of Ratings	7/28-09/30		
Range of Ratings (cfs)	0.001-397		
No. of Defining Measurements	7		
Rating Error (%)	9.0		

Rating Table No.			
Period of Ratings			
Range of Ratings (cfs)			
No. of Defining Measurements			
Rating Error (%)			

Table 5 Discussion (Rating Tables)

Four ratings were required to predict discharge for the water year. A moderately large event in November 2009 resulted in filling of the hydraulic control, warranting a shift from rating Table 9 to rating Table 10. A second smaller event in March 2009 scoured the hydraulic control resulting in the shift from rating Table 10 to Table 11. Seasonal baseflow filling of the hydraulic control warranted another rating shift from rating 11 back to rating Table 10.

Table 6. Model Summary

Model Type (Slope conveyance, other, none)	none
Range of Modeled Stage (feet)	
Range of Modeled Discharge (cfs)	
Valid Period for Model	
Model Confidence	

Table 6 Discussion (Modeled Data)

--

Table 7. Survey Type and Date (station, cross section, longitudinal)

Type	Date

Table 7 Discussion (Surveys)

--

Activities Completed

The Turbidity Threshold Sampling initiative is underway.
--